







G-BH7

Performance curve for Vacuum pump



Performance curve for Compressor



The performance curves are based on air at a temperature of 59 F and an atmospheric pressure of 401.53 inch H₂O with a tolerance of +/- 10 %. The total pressure differences are valid for suction and ambient temperatures up to 77 F. For other conditions please confer with us.

Each G-BH7 type can be applied both as vacuum pump and compressor in continuous operation over the total stated performance curve range. Blowers with ATEX 94/9 EG are available for the category 3D, 3G, 3/2D as well as 3/2G. The motors are available as standard for the input voltage of 50 and 60 Hz and for protection category IP 55 (IP 65 for category 3/2D). For the category 3/2G are only available blowers with the input voltage 50 and 60 Hz, respectively.

Selection and ordering data

Type 2BH7 420

Curve No.	Order No.	Fre-quency Hz	Rated power HP	Input voltage V	Input current A	Permissible total differential pressure ²⁾ inch H ₂ O	Sound pressure level ³⁾ dB(A)	Weight ca. lbs
-----------	-----------	---------------	----------------	-----------------	-----------------	---	--	----------------

ATEX-Category: 3D (Order-Option M35)

3~ 50/60 Hz, IP55, insulation material class F, temperature class T3

B 210g	2BH7420-0AD21-7-Z	50	2.0	230D	400Y	5.65D	3.25Y	-185	185	61	73
B 211g	2BH7420-0AD21-7-Z	60	2.35		460Y		3.2 Y	-177	173	66	73
B 214g	2BH7420-0AD61-7-Z	50	4.02	230D	400Y	10.61D	6.1 Y	-185	229	61	95
B 215g	2BH7420-0AD61-7-Z	60	4.62		460Y		5.9 Y	-177	269	66	95

ATEX-Category: 3G (Order-Option: M72)

3~ 50/60 Hz, IP55, insulation material class F, temperature class T3

B 210h	2BH7420-0AD21-7-Z	50	2.0	230D	400Y	5.65D	3.25Y	-185	185	61	73
B 211h	2BH7420-0AD21-7-Z	60	2.35		460Y		3.2 Y	-177	173	66	73
B 214h	2BH7420-0AD61-7-Z	50	4.02	230D	400Y	10.61D	6.1 Y	-185	229	61	95
B 215h	2BH7420-0AD61-7-Z	60	4.62		460Y		5.9 Y	-177	269	66	95

ATEX-Category: 3/2D (Order-Option: M34)

3~ 50/60 Hz, IP65, insulation material class F, temperature class T3

B 210k	2BH7420-0AD21-7-Z	50	2.0	230D	400Y	5.65D	3.25Y	-185	185	61	73
B 211k	2BH7420-0AD21-7-Z	60	2.35		460Y		3.2 Y	-177	173	66	73
B 214k	2BH7420-0AD61-7-Z	50	4.02	230D	400Y	10.61D	6.1 Y	-185	229	61	95
B 215k	2BH7420-0AD61-7-Z	60	4.62		460Y		5.9 Y	-177	269	66	95

ATEX-Category: 3/2G (Order-Option: M71)

3~ 50 Hz, IP55, insulation material class F, temperature class T3

B 210m	2BH7420-0AD21-7-Z	50	1.74	230D	400Y	5.0 D	2.9 Y	-169	157	61	73
B 214m	2BH7420-0AD61-7-Z	50	3.35	230D	400Y	9.2 D	5.3 Y	-185	229	61	93

3~ 60 Hz, IP55, insulation material class F, temperature class T3

B 211m	2BH7420-0AG21-7-Z	60	1.74		460Y		2.64Y	-132	112	66	73
B 215m	2BH7420-0AG61-7-Z	60	3.35		460Y		4.8 Y	-177	265	66	93



Other voltage ranges

2BH7420-0A □ . □ -Z

50Hz 60Hz



3~ ATEX

Category 3D, 3G and 3/2D

230 V D / 400 V Y	460 V Y	D 1
500 V D	575 V D	D 5
400 V D / 690 V Y	460 V D	D 6

Category 3/2G

230 V D / 400 V Y	---	D 1
500 V D	---	D 5
400 V D / 690 V Y	---	D 6
---	460 V Y	G 1
---	575 V D	G 5
---	460 V D	G 6

Further voltage range on request; please quote in plain text.

All G-BH7 achieve the standards and norms of the low voltage directive 72/23/EWG, rotating electrotechnical motor EN 60034-1-34, electromagnetic compatibility (EMC) DIN EN 61000-3-6/-4.

²⁾ Relief-valve are available for limiting differential pressure.

³⁾ Measuring-surface sound-pressure level acc. to DIN EN 21680, measured at a distance of 3.28 ft. The pump is throttled to an average suction pressure, a hose is connected to the discharge side (vacuum pump) / suction side (compressor), but is not fitted with relief valves.

The motors are designed according to the DIN EN 60 034 / DIN IEC 34-1 and temperature class F.

For the three phase machines the tolerances are +/- 10 % for fixed voltage. The frequency tolerance is maximum +/- 2 %.

Changes in particular the quoted performance curve, datas and weights without prior notice. The figures are without obligations.

**Gardner
Denver**

Elmo Rietschle is a brand of the
Gardner Denver Blower Division

info@de.gardnerdenver.com
www.gd-elmorietschle.com

Gardner Denver Schopfheim GmbH

Roggensbachstr. 58
79650 Schopfheim · Germany
Tel. +49 7622 392-0
Fax +49 7622 392-300

Gardner Denver Deutschland GmbH

Industriestr. 26
97616 Bad Neustadt · Germany
Tel. +49 9771 6888-0
Fax +49 9771 6888-4000