





**Elmo
Rietschle**

G-BH1

Data sheet 2BH1 610


Side channel blower



Performance curves

Vacuum operation (acfm)

Pressure operation (scfm)



The performance curves are based on air at a temperature of 59 F and an atmospheric pressure of 29.91 inch Hg with a tolerance of ± 10 %. The total pressure differences are valid for inlet and ambient temperature up to 77 F. Suction capacity relates to inlet conditions. Pressure capacity relates to atmospheric conditions. For other conditions please get in touch with us.

Every G-BH blower can be used either for vacuum or pressure in continuous operation over the total performance curve range. The motors are available as standard in protection category IP 55 and insulation class F. These blowers are UL and CSA approved.

Selection and ordering data

Type 2BH1 610

No.	Fre- quency	Rated			Max. differential pressure ²⁾		Sound pressure level ³⁾	Weight Approx.	Order No.
		Voltage ¹⁾	Current	Power	Vacuum	Pressure			
3~ 50/60 Hz, IP55, Insulation material class F, UL 507 and CSA 22.2 No 113 (certificate number E225239)									
1	50	200-240 Δ / 345-415 Y	9.7 Δ / 5.6 Y	3.0	-80	76	73	95	2BH1610-7HH16
	60	220-275 Δ / 380-480 Y	10.3 Δ / 6 Y	3.4	-68	60	75		
2	50	200-240 Δ / 345-415 Y	12.5 Δ / 7.2 Y	4.0	-100	100	73	110	2BH1610-7HH26
	60	220-275 Δ / 380-480 Y	12.6 Δ / 7.3 Y	4.6	-84	72	75		
3	50	200-240 Δ / 345-415 Y	17.3 Δ / 10 Y	5.8	-145	145	73	115	2BH1610-7HH36
	60	220-275 Δ / 380-480 Y	18.0 Δ / 10.4 Y	6.4	-132	128	75		
4	50	200-240 Δ / 345-415 Y	23.0 Δ / 13.3 Y	7.4	-169	201	73	179	2BH1610-7HH46
	60	220-275 Δ / 380-480 Y	23.0 Δ / 13.3 Y	8.4	-177	177	75		
5	50	345-415 Δ / 600-720 Y	16.7 Δ / 9.6 Y	10.1	-169	245	73	190	2BH1610-7HH57
	60	380-480 Δ	17.3 Δ	11.5	-177	269	75		
3~ 50/60 Hz, IP55, Insulation material class F, UL 507 and CSA 22.2 No 113 (certificate number E225239)									
1	50	500 Y	4.5 Y	3.0	-80	76	73	95	2BH1610-7HC13
	60	575 Y	4.55 Y	3.4	-68	60	75		
2	50	500 Δ	5.8 Δ	4.0	-100	100	73	110	2BH1610-7HC25
	60	575 Δ	6.0 Δ	4.6	-84	72	75		
3	50	500 Δ	7.5 Δ	5.4	-145	145	73	115	2BH1610-7HC35
	60	575 Δ	7.6 Δ	6.2	-132	128	75		
4	50	500 Δ	10.5 Δ	7.4	-169	201	73	179	2BH1610-7HC45
	60	575 Δ	10.4 Δ	8.4	-177	177	75		
5	50	500 Δ	13.0 Δ	10.1	-169	245	73	190	2BH1610-7HC55
	60	575 Δ	13.6 Δ	11.5	-177	269	75		

1) In case of frequency converter operation the standard motor insulation system is suitable for converter input voltages up to 460 V.

2) Relief valves available for limiting differential pressure.

3) Measuring surface sound pressure level acc. to EN ISO 3744, measured with an equivalent unit at a distance of 1 m. The pump is throttled to an average suction pressure, with piping connected, but no relief valves fitted, tolerance ±3 dB (A).

All G-BH match the 2006/42/EC (machinery) and 2006/95/EC (low voltage) directives and the EN 60034-1 norm "Rotating electrical machines".

The motors comply with EN 60 034-1 / -2 / -30 (IEC 60034) and thermal class F.

For three phase motors tolerances are +/-10% for fixed voltage motors and +/-5% for voltage range motors. Single phase machines are designed with a +/- 5% tolerance.

The frequency tolerance is +/- 2 % maximum.

Motors for other mains

Voltage range		Fixed voltage		VFD	c us					
50 Hz	60 Hz	50 Hz	60 Hz	87 Hz	60 Hz		2BH1610-7. □ . □			
					Δ	Y				
3~										
185 - 225 V Δ / 320 - 390 V Y	200 - 240 V Δ / 345 - 415 V Y			380 V Δ	•	•	H	1		
200 - 240 V Δ / 345 - 415 V Y	220 - 275 V Δ / 380 - 480 V Y				•	•			H	6
345 - 415 V Δ / 600 - 720 V Y	380 - 480 V Δ / 660 - 720 V Y				•	•			H	7
		500 V Δ	575 V Y		•	•			C	3
							C	5		
3~										
IE2 3~ ⁵⁾										
180 - 240 V Δ / 310 - 415 V Y	200 - 275 V Δ / 345 - 480 V Y	200 V Δ / 345 V Y	230 V Δ / 400 V Y	400 V Δ	•	•	P	1		
450 - 550 V Y	520 - 600 V Y	500 V Y	575 V Y		•	•			P	3
450 - 550 V Δ	520 - 600 V Δ	500 V Δ	575 V Δ		•	•			P	5
200 - 260 V Δ / 350 - 450 V Y	230 - 290 V Δ / 400 - 500 V Y	230 V Δ / 400 V Y	265 V Δ / 460 V Y		•	•			P	6
350 - 450 V Δ / 610 - 725 V Y	400 - 500 V Δ / 690 - 725 V Y	400 V Δ / 690 V Y	460 V Δ	•	•	P	7			

5) Performance can differ if IE2 motors are used. Please refer to corresponding data sheets.

Changes in particular of the quoted performance curve, data and weights may occur without prior notice. The data given do not constitute an obligation from our side to deliver as shown.

Elmo Rietschle is a brand of Gardner Denver

**Gardner
Denver**

Your Ultimate Source for Vacuum and Pressure

Gardner Denver Deutschland GmbH

Industriestraße 26
97616 Bad Neustadt - Germany
Tel.: +49 9771 6888-0
Fax: +49 9771 6888-4000

www.gd-elmoietschle.com • er.de@gardnerdenver.com

Gardner Denver, Inc.

1800 Gardner Expressway
Quincy, IL 62305
Tel: 217-222-5400
Fax: 217-221-8780